



## AIRCRETE THERMAL BLOCKS - DECLARATION OF PERFORMANCE

**DOP Ref:** Mannok Aircrete High Ten -100x100mm Soap Bar

1. Unique Identification code of Product type: Mannok Aircrete Thermal Blocks -100x100mm High Ten Soap Bar (GPLM)
2. Type, Batch or Serial Number or any other Element allowing identification of the Product: See Point 1
3. Intended use or uses of the product, in accordance with the applicable harmonised technical specification: For use in the construction of load bearing and non-loadbearing solid internal and external walls, above and below the damp proof course and the inner and outer leaves of cavity walls
4. Name and registered address of manufacturer: Mannok Build Ltd, 187 Ballyconnell Rd, Derrylin, Co. Fermanagh, Northern Ireland, BT92 9GP
5. Where applicable, name and contact address of the authorised representative whose mandate covers tasks specified in Article 12(2): Not Applicable
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V: System 2+
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: The notified product certification body, NSAI (Notified Body reference no. 0050) has performed the initial inspection of the manufacturing plant and of factory production control, the continuous surveillance, assessment and evaluation of factory production control before placing the product on the market under system 2+ and issued the certificate of constancy of performance.
8. Declared Performance: Refer to table attached
9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Essential Characteristics		Performance	Harmonised Technical Specification
Dimensions <i>mm</i>	Length	440	BS EN 771-4:2011+A1:2015
	Width	100	
	Height	100	
Configuration		Solid Group 1	
Dimensional Tolerances		GPLM	
Compressive Strength unit category		I	
Mean Compressive Strength $N/mm^2$		9.0	
Dimensional Stability (Shrinkage) $mm/m$		0.4	
Shear Bond Strength $N/mm^2$		0.15 (Annex C BS EN 998-2)	
Flexural Bond Strength $N/mm^2$		NPD	
Reaction to Fire		Euroclass A1	
Water Absorption $g/m^2s^{0.5}$		NPD	
Water Vapour Diffusion coefficient $\mu$		5/10 (Tabulated values BS EN 1745)	
Durability against freeze thaw		NPD	
Gross Dry Density $Kg/m^3$		800	
Thermal Conductivity $W/m.k$		0.19 ( $\lambda_{10,dry}$ )	
Dangerous Substances		See footnote	
Note: Information on dangerous substances will only be given when and where required in the appropriate form. See Annex ZA.3 of BS EN 771-4:2011			

Liam McCaffrey, CEO  
16th November 2020



20

187 Ballyconnell Road, Derrylin,  
Co. Fermanagh, Northern Ireland, BT92 9GP  
0050-CPR-0971

EN771-4:2011+A1:2015  
9.0N 100mmx100mm Soap Bar (Aircrete High Ten Block)  
Category 1 – 440mm, 100mm, 100mm

<b>Dimensions</b>	Declared Value	(L x W x H) 440mm, 100mm, 100mm
<b>Dimensional Tolerances</b>	Declared Category	GPLM
<b>Configuration</b>	Declared	Solid Group 1 unit to I.S EN 1996-1
<b>Compressive Strength</b>	Characteristic	9.0N/mm <sup>2</sup>
<b>Dimensional Stability</b> Moisture Movement	Declared Value	0.4mm/m
<b>Bond Strength</b> Shear Bond Strength	Declared Value	0.15N/mm <sup>2</sup> (I.S EN 998-2) (Tabulated Value)
Flexural Bond Strength	Declared Value	NPD
<b>Reaction to Fire</b>	Declared Class	Euroclass A1 (I.S EN 1996-1-2 Annex A) (Tabulated Value)
<b>Water Absorption</b>	Declared Value	NPD
<b>Water Vapour Permeability</b>	Declared Value	5/10 $\mu$ (I.S EN 1745 Annex A) (Tabulated Value)
<b>Direct Airborne Sound Insulation</b> Gross Dry Density Configuration	Declared Declared	800 kg/m <sup>3</sup>
<b>Thermal Conductivity</b>	Declared Value	0.19 W/mK ( $\lambda_{10}$ , dry Mat)(I.S. EN 1745 Annex A) (Tabulated Value)
<b>Durability against Freeze Thaw</b>	Declared	NPD (Not left to be exposed)
<b>Dangerous Substances</b>	Declared	Information on dangerous substances will only be given when and where required in the appropriate form. See annex ZA.3 of BS EN 771-4:2011

