



MANNOK

Mannok IsoFrame

Mannok IsoFrame board is one of the range of PIR (polyisocyanurate foam boards we manufacture for the insulation of floors, walls and roofs.

Benefits of Mannok IsoFrame

- IsoFrame rigid insulation is designed for use in structural Steel/Timber Framed cavity wall construction on new build projects.
- The low emissivity facings improve the thermal performance of the cavity and reduce the U-value of the wall.
- Mannok IsoFrame has a low thermal conductivity, minimising the thickness required to achieve the design U-value while maintaining a clear cavity.
- Mannok IsoFrame has good dimensional tolerances, enabling boards to be tightly butted to form a continuous layer of insulation.
- Mannok IsoFrame has been tested BS EN 1365-1:2012. Fire Resistance for Loadbearing Elements.

Composition

Mannok IsoFrame consists of a core of PIR foam with bonded foil facings. The gas filled cells give IsoFrame its high thermal performance and strength while the foil facings maximises performance.


Thermal Performance

Mannok IsoFrame has a thermal conductivity of 0.022W/ mK, making it one of the most effective rigid board insulations available.


Environmental

Mannok PIR Insulation has an ozone depletion potential (ODP) of zero and a Global Warming Potential (GWP) of less than 5, certified to ISO 14001 - Environmental Management Systems. Mannok Therm Cavity / MC achieved an A+ rating when compared to the BRE Green Guide.

Applications



Cavity walls:
Mannok Therm Wall / MW in timber frame*



Cavity walls:
Mannok Therm Wall / MW in steel stud frame

CE Marking



Construction Products Regulation (CPR) requires mandatory CE marking for all thermal insulation products. IsoFrame boards are CE marked to harmonised standard EN 13165. The Declaration of Performance, 011/20 is available on our website link. (see bottom of page for link)

Delivery & Storage

Mannok PIR Insulation boards are shrinkwrapped in clear polyethylene for delivery to site. Each pack is labelled with the product description, product characteristics, manufacturer's name and brand name, quantity per pack, and any identification marks.

Biological / Chemical

Mannok PIR Insulation does not rot and does not support mould or fungus. Mannok PIR Insulation is chemically inert, and poses no threat to anyone using it.

Technical Support

Mannok provides a comprehensive technical support service for designers and contractors.

Mannok can provide:

- copies of Agrément and test certificates
- U-value calculations
- interstitial risk calculations
- design advice
- guidance on the most effective ways to meet current Building Regulations and Building Standards.

Contact Technical Support:

- Call: +44 (0) 28 6774 8866
- Email: technical@mannokbuild.com

Physical & Performance Characteristics

Surface	Composite foil facings
Edge:	Butt
Thicknesses:	20-200mm
Length x width:	1200mm x 2400mm
Thermal conductivity	0.022W/mK
Core water vapour resistivity	≈300MNs/gm
Compressive strength:	>150kPa

Fire Performance

Thickness	BS 476-7	BS EN 13501-1
20-200mm	Class 1	Euroclass E

Dimensional stability / Durability

When tested to EN 1604 Mannok PIR Insulation achieves level DS(TH)4 to EN 13165.

Mannok PIR Insulation will perform for the service life of the building.

Design and Installation

For design and installation information plus thicknesses of Mannok IsoFrame to achieve specific U-values in all cavity wall applications, consult our Product & Installation Guide, available via our website.

For further information:

Mannok, Derrylin, Co. Fermanagh, Northern Ireland BT92 9GP

t: +44 (0) 28 6774 8866 | www.mannokbuild.com | info@mannokbuild.com



Every effort has been taken in the preparation of this data sheet to ensure the accuracy of representations contained herein. Recommendations as to the use of materials, construction details and methods of installation are given in good faith and relate to typical situations. However, every site has different characteristics and reliance should not be placed upon the foregoing recommendations. Advice can be given as to specific applications of the products, upon request to Mannok.