



PIR INSULATION - DECLARATION OF PERFORMANCE

DOP Number: 009/20

Designation Code: PIR-EN 13165- T2-W2-L2-DS(TH)4-DS(-20)2-WL(T)2-CS(10/Y)150

1. Unique Identification code of Product type

Mannok Therm Roof / MFR-DPFR - Insulated Dual Purpose Flat Roof Board

2. Type, Batch or Serial Number or any other Element allowing identification of the Product

Dual Purpose Flat Roof - PIR Rigid insulation with Gas Open Facings (Glass Fibre Backed Facing on one side and Bitumen Backed Facing on the other side).

3. Intended use or uses of the product, in accordance with the applicable harmonized technical specification

PIR Thermal Insulation board for the construction Industry

4. Name and registered address of manufacturer

Mannok Insulation Ltd,
Scotchtown, Ballyconnell,
Co Cavan, Ireland

5. System or systems and verification of constancy of performance of the product as set out in AVCP System 3

6. Covered by harmonised standard
EN 13165

7. Name and address of the notified bodies determining product-type on the basis of type testing

BRE Global, Bucknalls Lane,
Watford, Herts, WD259XX, UK

British Board of Agrément,
PO Box 195, Bucknalls Lane,
Garston, Herts WD2598A, UK

8. Notified Testing Laboratory Number
BRE Test No: 0832

Notified Testing Laboratory Number
BBA Test No: 0836



9. Declared Performances

Essential Characteristic	Performance		Harmonised Technical Specification
Reaction to Fire	Euro Class F		EN 13501-1
Thermal Resistance	RD ((m ² .K)/W)		EN 12939
Thermal Conductivity	W/mK		EN12667
Compressive Strength	kPa		EN826
Long Term Water Absorption			EN13950
Length & Width	mm	1200 x 600	EN822
PIR Thickness	d ^N		EN 823
Squareness	mm/m		EN824
Flatness	mm		EN825
Release of Dangerous substances	No harmonised test method available		
Flexural Strength	No performance declared.		
Tensile Strength Perpendicular to Faces	No performance declared.		EN1607
Durability of reaction to fire against heat, weathering, aging/ degradation	Reaction to Fire does not change over time		
Dimensional stability under specified temperature and humidity conditions	DS(TH)4 & DS(-20,-)2		EN1604

EN 13165

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Name and position held by the person empowered to sign the declaration on behalf of the manufacturer.

Liam McCaffrey CEO
16th November 2020