



# PIR INSULATION - DECLARATION OF CONFORMITY

**DOP Reference:** 010/20

**Designation Code:** PIR-EN 13165- T2-W2-L2-DS(TH)4-DS(-20)2-WL(T)2-CS(10/Y)150

## 1. Unique Identification code of Product type

Mannok IsoShield - Full Fill Cavity Wall Insulation

## 2. Type, Batch or Serial Number or any other Element allowing identification of the Product

Therm IsoShield Full Fill - 72mm, 97mm, 122mm, 147mm

## 3. Intended use or uses of the product, in accordance with the applicable harmonised technical specification

PIR Thermal Insulation board for the construction Industry

## 4. Name and registered address of manufacturer

Mannok Insulation Ltd,  
Scotchtown, Ballyconnell,  
Co Cavan, Ireland

## 5. System or systems and verification of constancy of performance of the product as set out in

AVCP System 3

## 6. Covered by harmonised standard

BS EN 13165

## 7. Name and address of the notified bodies determining product-type on the basis of type testing

LGAI Tech centre S.A./ Applus  
Campus UAB, Apto Correos 08193  
Bellaterra, Spain  
Notified body no. 0370

British Board of Agrément,  
PO Box 195, Bucknalls Lane,  
Garston, Herts WD2598A, UK  
Notified body no. 0836



## 9. Declared Performances

Essential Characteristic	Performance		Harmonised Technical Specification	
Reaction to Fire	Euro Class E		<b>BS EN 13165</b>	BS EN 13501-1
Thermal Resistance	RD ((m <sup>2</sup> .K)/W)			BS EN 12939
Thermal Conductivity	W/mK			BS EN12667
Compressive Strength	kPa			BS EN826
Long Term Water Absorption				BS EN13950
Length & Width	mm	450 x 1200		BS EN822
PIR Thickness	d <sup>N</sup>			BS EN 823
Squareness	mm/m			BS EN824
Flatness	mm			BS EN825
Release of Dangerous substances	No harmonised test method available			
Flexural Strength	No performance declared.			
Tensile Strength Perpendicular to Faces	No performance declared.			BS EN1607
Durability of reaction to fire against heat, weathering, aging/ degradation	Reaction to Fire does not change over time			
Dimensional stability under specified temperature and humidity conditions	DS(TH)4 & DS(-20,-)2		BS EN1604	

10. The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Name and position held by the person empowered to sign the declaration on behalf of the manufacturer.



Liam McCaffery

CEO

21<sup>st</sup> November 2022